
Symmetry Vertical Platform Lift

Model VPC-UL

Vertical Platform Conveyance-Unenclosed Lift



 **symmetry**
More space for living.



www.symmetryelevator.com

Convenient access to all levels

Whether it's commercial or residential use, outdoors or indoors, Symmetry vertical platform lifts eliminate the barrier that stairs can cause for people with limited mobility. A cost-effective solution, platform lifts create convenient access without compromising architectural character.

Designed for ease of installation, Symmetry platform lifts are equipped with an "articulating" base and carriage design, allowing the unit to be folded to a width of 21 inches without removal of the carriage.

Standard Features

- 750-lb. capacity
- Speed: 10 FPM with a 1 HP, 115-volt motor
- Lifting height: up to 60 inches for commercial applications and 168 inches for residential applications
- Steel constructed with electrostatic, powder-coated finish
- On-board diagnostics
- Constant pressure up/down control switch installed on the platform
- Constant pressure, elevator-style, hall call control stations provided at each landing

Optional Features

- 230-volt motor
- Remote mounted controller
- ADA phone for both indoor and outdoor models
- Emergency lights
- Key switch to lock platform
- Flip-up ramp
- Battery Back-up

Safety Features

- Nonskid platform surface
- Obstruction safety panel under platform (when not installed within a runway enclosure)
- Alarm and emergency stop switch
- Grab rail
- Landing interlocks keep door locked when the lift is on another floor
- Upper final limit

Platform Sizes

- 36" W x 48" D
- 36" W x 54" D
- 36" W x 60" D
- 42" W x 60" D

Exit Configurations

- Straight through
- 90°

Vertical Platform Lift Gate/Door Options

- 42" platform gate*
- 42" landing gate*
- 80" landing gate*
- Non-fire-rated red oak door**
- Fire-rated steel door

*Available with optional acrylic insert

**Also available in other wood choices, by request

Platform Walls and Surfaces Color Options (floor is black nonskid surface)

- Ivory (standard)
- White (optional)
- Gray (optional)
- Black (optional)

Choose from a stationary or a more compact folding ramp, depending on your space requirements.

Symmetry platform lifts come with a two-year limited parts warranty on the basic unit, including

The information contained on this chart is intended for layout design only and should not be used for construction. Please contact the local representative for a job specific drawing.

| Straight through configuration | | | | |
|--------------------------------|-----------------|------------------|-----------|------------|
| Nominal Platform Size | Equipment Width | Equipment Length | Pit Width | Pit Length |
| 36" x 48" | *48 1/2" | **48" | *51 1/2" | 49 1/2" |
| 36" x 54" | *48 1/2" | **54" | *51 1/2" | 55 1/2" |
| 36" x 60" | *48 1/2" | **60" | *51 1/2" | 61 1/2" |
| 42" x 60" | *54 1/2" | **60" | *57 1/2" | 61 1/2" |
| 90° configuration | | | | |
| 42" x 60" | *54 1/2" | **60" | *55 1/4" | 63 1/2" |

* Additional 1" equipment width required when supplied with a platform gate that is hinged on the same side as the main tower.

** Equipment length increases when supplied with a ramp
 Note: 36" x 48" platform size is not available with a platform gate option.

Footprint Layout

The diagram illustrates the footprint layout of the platform lift. It shows a rectangular pit with a 'Main Tower' on the right side. Dimensions are labeled as follows: Pit Length (total length of the pit), Equipment Length (length of the lift platform), Equipment Width (width of the lift platform), Pit Width (total width of the pit including the tower), and Pit Length (total length of the pit). A note states: 'Pit width and length include running clearances. If equipment will be installed in a pit, recommended pit depth is 3".'

Straight Through Unenclosed Configuration Shown

90° Unenclosed Configuration Shown



More space for living.

877.375.1428 | symmetryelevator.com